PTG-4001

Safety Data Sheet PTG-4001

This SDS conforms to U.S. Code of Federal Regulations 29 CFR 1910.1200, Hazard Communication.
Prepared for Canada according to the Hazardous Products Regulation (February 11, 2015).

Issue date: 05/05/2015 Revision date: 05/17/2024 Supersedes: 02/21/2022 Version: 1.4

SECTION 1: Identification

1.1. Product identifier

Product form : Mixture

Product name : PTG-4001

Formula : (0.00001 - 0.9999 %) Hydrogen Sulfide, (0.0001 - 0.0999 %) Carbon Monoxide, (0.0001 - 3.5 %) Methane, (0.0001 - 19.5 %) Oxygen in Nitrogen.

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Industrial use; Use as directed.

Recommended use and restrictions on use : Calibration / Reference

1.3. Details of the supplier of the safety data sheet

USA:
PortaGas, a Linde Company
(Linde Gas & Equipment LLC.),
1202 E Sam Houston Pkwy S
Pasadena, TX 77503
T +1 713-928-6477 - F +1 713-928-9961
PDImsds@Praxair.com

Canada:
Linde Canada
5015 Spectrum Way, Suite 500
Mississauga, Ontario, L4W 0E4
1-800-225-8247

1.4. Emergency telephone number

Emergency number : Onsite Emergency: 1-800-645-4633

CHEMTREC, 24hr/day 7days/week
— Within USA: 1-800-424-9300, Outside USA: 001-703-527-3887
(collect calls accepted, Contract 17729)

SECTION 2: Hazard identification

2.1. Classification of the substance or mixture

GHS US classification

Press. Gas (Comp.) H280
Simple asphyxiant SIAS

2.2. Label elements

GHS US labeling

Hazard pictograms (GHS US) :



GHS04

Signal word (GHS US) : Warning

Hazard statements (GHS US) : H280 - CONTAINS GAS UNDER PRESSURE; MAY EXPLODE IF HEATED
OSHA-H01 - MAY DISPLACE OXYGEN AND CAUSE RAPID SUFFOCATION

Precautionary statements (GHS US) : P403 - Use and store only outdoors or in a well-ventilated place.
CGA-PG21 - Open valve slowly.
CGA-PG12 - Do not open valve until connected to equipment prepared for use.
CGA-PG11 - Never put cylinders into unventilated areas of passenger vehicles.
CGA-PG10 - Use only with equipment rated for cylinder pressure.
CGA-PG06 - Close valve after each use and when empty.
CGA-PG05 - Use a back flow preventive device in the piping.
CGA-PG02 - Protect from sunlight when ambient temperature exceeds 52°C (125°F).

Linde and the Linde wordmark are trademarks or registered trademarks of Linde plc or its affiliates. The information contained herein is offered for use by technically qualified personnel at their discretion and risk without warranty of any kind.

Copyright © 2024, Linde Inc.

2.3. Other hazards

2.4. Unknown acute toxicity (GHS US)

SECTION 2: Hazard identification

2.1. Classification of the substance or mixture

GHS-CA classification

Gases under pressure Compressed gas H280

2.2. GHS Label elements, including precautionary statements

GHS-CA labelling

Hazard pictograms :



GHS04

Signal word : Warning

Hazard statements : CONTAINS GAS UNDER PRESSURE; MAY EXPLODE IF HEATED

Precautionary statements : Use and store only outdoors or in a well-ventilated place.
Open valve slowly.
Do not open valve until connected to equipment prepared for use.
Never put cylinders into unventilated areas of passenger vehicles.
Use only with equipment rated for cylinder pressure.
Close valve after each use and when empty.
Use a back flow preventive device in the piping.
Protect from sunlight when ambient temperature exceeds 52°C (125°F).

2.3. Other hazards

2.4. Unknown acute toxicity (GHS CA)

SECTION 3: Composition/Information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	Common Name (Synonyms)
Nitrogen	(CAS-No.) 7727-37-9	75.9002 – 100	Nitrogen gas / NITROGEN / Nitrogen, compressed
Oxygen	(CAS-No.) 7782-44-7	0.0001 – 19.5	Oxygen (dissolved) / Oxygen gas / Oxygen, compressed / Oxygen, dissolved
Methane	(CAS-No.) 74-82-8	0.0001 – 3.5	Marsh gas / Natural gas, refrigerated liquid / Methane, compressed
Hydrogen sulfide	(CAS-No.) 7783-06-4	0.0001 – 1	Hydrogen sulfide (H2S) / Hydrogen sulphide / Sulfur hydride / Sulfureted hydrogen / Dihydrogen sulphide / Hydrogensulfide
Carbon monoxide	(CAS-No.) 630-08-0	0.0001 – 0.0999	Carbon monoxide, compressed / Compressed carbon monoxide / Carbon oxide (CO) / Carbon(II) oxide / Carbon oxide

Name	Product identifier	%	Common Name (Synonyms)
Nitrogen	(CAS-No.) 7727-37-9	75.9002 – 100	Nitrogen gas / NITROGEN / Nitrogen, compressed

Linde and the Linde wordmark are trademarks or registered trademarks of Linde plc or its affiliates. The information contained herein is offered for use by technically qualified personnel at their discretion and risk without warranty of any kind.

Copyright © 2024, Linde Inc.

Name	Product identifier	%	Common Name (Synonyms)
Oxygen	(CAS-No.) 7782-44-7	0.0001 – 19.5	Oxygen (dissolved) / Oxygen gas / Oxygen, compressed / Oxygen, dissolved
Methane	(CAS-No.) 74-82-8	0.0001 – 3.5	Marsh gas / Natural gas, refrigerated liquid / Methane, compressed
Hydrogen sulfide	(CAS-No.) 7783-06-4	0.0001 – 1	Hydrogen sulfide (H2S) / Hydrogen sulphide / Sulfur hydride / Sulfureted hydrogen / Dihydrogen sulphide / Hydrogensulfide
Carbon monoxide	(CAS-No.) 630-08-0	0.0001 – 0.0999	Carbon monoxide, compressed / Compressed carbon monoxide / Carbon oxide (CO) / Carbon(II) oxide / Carbon oxide

Hydrogen sulfide (7783-06-4)	
WHMIS Classification	Class A - Compressed Gas Class B Division 1 - Flammable Gas Class D Division 1 Subdivision A - Very toxic material causing immediate and serious toxic effects Class D Division 2 Subdivision B - Toxic material causing other toxic effects

Carbon monoxide (630-08-0)	
WHMIS Classification	Class A - Compressed Gas Class B Division 1 - Flammable Gas Class D Division 1 Subdivision A - Very toxic material causing immediate and serious toxic effects Class D Division 2 Subdivision A - Very toxic material causing other toxic effects

Oxygen (7782-44-7)	
WHMIS Classification	Class A - Compressed Gas Class C - Oxidizing Material

Nitrogen (7727-37-9)	
WHMIS Classification	Class A - Compressed Gas

Methane (74-82-8)	
WHMIS Classification	Class A - Compressed Gas Class B Division 1 - Flammable Gas

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures after inhalation : Remove to fresh air and keep at rest in a position comfortable for breathing. If not breathing, give artificial respiration. If breathing is difficult, trained personnel should give oxygen. Call a physician.

First-aid measures after skin contact : Adverse effects not expected from this product.

First-aid measures after eye contact : Immediately flush eyes thoroughly with water for at least 15 minutes. Hold the eyelids open and away from the eyeballs to ensure that all surfaces are flushed thoroughly. Contact an ophthalmologist immediately.

First-aid measures after ingestion : Ingestion is not considered a potential route of exposure.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects : Effects are due to lack of oxygen. Moderate concentrations may cause headache, drowsiness, dizziness, excitation, excess salivation, vomiting, and unconsciousness. Prolonged exposure to low concentrations of carbon monoxide can kill. Inhalation.

4.3. Indication of any immediate medical attention and special treatment needed

None.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : Use extinguishing media appropriate for surrounding fire.

5.2. Special hazards arising from the substance or mixture

Fire hazard : Not flammable.

Explosion hazard : Heat may build pressure, rupturing closed containers, spreading fire and increasing risk of burns and injuries.

Reactivity : No reactivity hazard other than the effects described in sub-sections below.

Linde and the Linde wordmark are trademarks or registered trademarks of Linde plc or its affiliates. The information contained herein is offered for use by technically qualified personnel at their discretion and risk without warranty of any kind.

Copyright © 2024, Linde Inc.

5.3. Advice for firefighters

Firefighting instructions	:	Evacuate all personnel from the danger area. Use self-contained breathing apparatus (SCBA) and protective clothing. Immediately cool containers with water from maximum distance. Stop flow of gas if safe to do so, while continuing cooling water spray. Remove ignition sources if safe to do so. Remove containers from area of fire if safe to do so. On-site fire brigades must comply with OSHA 29 CFR 1910.156 and applicable standards under 29 CFR 1910 Subpart L—Fire Protection.
Special protective equipment for fire fighters	:	Standard protective clothing and equipment (Self Contained Breathing Apparatus) for fire fighters.
Other information	:	Containers are equipped with a pressure relief device. (Exceptions may exist where authorized by DOT.).

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Emergency procedures : Evacuate unnecessary personnel.

6.1.2. For emergency responders

6.2. Environmental precautions

Prevent waste from contaminating the surrounding environment. Prevent soil and water pollution. Dispose of contents/container in accordance with container supplier/owner instructions.

6.3. Methods and material for containment and cleaning up

6.4. Reference to other sections

See also sections 8 and 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling	:	Wear leather safety gloves and safety shoes when handling cylinders. Protect cylinders from physical damage; do not drag, roll, slide or drop. While moving cylinder, always keep in place removable valve cover. Never attempt to lift a cylinder by its cap; the cap is intended solely to protect the valve. When moving cylinders, even for short distances, use a cart (trolley, hand truck, etc.) designed to transport cylinders. Never insert an object (e.g, wrench, screwdriver, pry bar) into cap openings; doing so may damage the valve and cause a leak. Use an adjustable strap wrench to remove over-tight or rusted caps. Slowly open the valve. If the valve is hard to open, discontinue use and contact your supplier. Close the container valve after each use; keep closed even when empty. Never apply flame or localized heat directly to any part of the container. High temperatures may damage the container and could cause the pressure relief device to fail prematurely, venting the container contents. For other precautions in using this product, see section 16.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Comply with applicable regulations.

Linde and the Linde wordmark are trademarks or registered trademarks of Linde plc or its affiliates. The information contained herein is offered for use by technically qualified personnel at their discretion and risk without warranty of any kind.

Copyright © 2024, Linde Inc.

Storage conditions	:	Store in a cool, well-ventilated place. Store and use with adequate ventilation. Store only where temperature will not exceed 125°F (52°C). Firmly secure containers upright to keep them from falling or being knocked over. Install valve protection cap firmly in place by hand. Store full and empty containers separately. Use a first-in, first-out inventory system to prevent storing full containers for long periods. **OTHER PRECAUTIONS FOR HANDLING, STORAGE, AND USE:** When handling product under pressure, use piping and equipment adequately designed to withstand the pressures to be encountered. Never work on a pressurized system. Use a back flow preventive device in the piping. Gases can cause rapid suffocation because of oxygen deficiency; store and use with adequate ventilation. If a leak occurs, close the container valve and blow down the system in a safe and environmentally correct manner in compliance with all international, federal/national, state/provincial, and local laws; then repair the leak. Never place a container where it may become part of an electrical circuit.

7.3. Specific end use(s)

None.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

PTG-4001	
ACGIH	Not applicable
OSHA	Not applicable

Hydrogen sulfide (7783-06-4)		
ACGIH	ACGIH OEL TWA	1 ppm
ACGIH	ACGIH OEL STEL	5 ppm
OSHA	OSHA PEL C	20 ppm

Carbon monoxide (630-08-0)		
ACGIH	ACGIH OEL TWA	25 ppm
OSHA	OSHA PEL TWA	55 mg/m³
OSHA	OSHA PEL TWA	50 ppm

Oxygen (7782-44-7)	
ACGIH	Not applicable
OSHA	Not applicable

Nitrogen (7727-37-9)	
ACGIH	Not applicable
OSHA	Not applicable

Methane (74-82-8)	
ACGIH	Not applicable
OSHA	Not applicable

Hydrogen sulfide (7783-06-4)		
ACGIH	ACGIH OEL TWA	1 ppm
ACGIH	ACGIH OEL STEL	5 ppm
OSHA	OSHA PEL C	20 ppm
IDLH	IDLH	100 ppm
NIOSH	NIOSH REL C	15 mg/m³

Linde and the Linde wordmark are trademarks or registered trademarks of Linde plc or its affiliates. The information contained herein is offered for use by technically qualified personnel at their discretion and risk without warranty of any kind.

Copyright © 2024, Linde Inc.

Hydrogen sulfide (7783-06-4)		
NIOSH	NIOSH REL C	10 ppm

Alberta	OEL C	21 mg/m³
Alberta	OEL C	15 ppm
Alberta	OEL TWA	14 mg/m³
Alberta	OEL TWA	10 ppm
British Columbia	OEL C	10 ppm
Manitoba	OEL STEL	5 ppm
Manitoba	OEL TWA	1 ppm
New Brunswick	OEL STEL	21 mg/m³
New Brunswick	OEL STEL	15 ppm
New Brunswick	OEL TWA	14 mg/m³
New Brunswick	OEL TWA	10 ppm
Newfoundland & Labrador	OEL STEL	5 ppm
Newfoundland & Labrador	OEL TWA	1 ppm
Nova Scotia	OEL STEL	5 ppm
Nova Scotia	OEL TWA	1 ppm
Nunavut	OEL C	28 mg/m³
Nunavut	OEL C	20 ppm
Nunavut	OEL STEL	21 mg/m³
Nunavut	OEL STEL	15 ppm
Nunavut	OEL TWA	14 mg/m³
Nunavut	OEL TWA	10 ppm
Northwest Territories	OEL STEL	15 ppm
Northwest Territories	OEL TWA	10 ppm
Ontario	OEL TWAEV	15 ppm
Ontario	OEL TWAEV	10 ppm
Prince Edward Island	OEL STEL	5 ppm
Prince Edward Island	OEL TWA	1 ppm
Québec	VECD (OEL STEV)	21 mg/m³
Québec	VECD (OEL STEV)	15 ppm
Québec	VEMP (OEL TWAEV)	14 mg/m³
Québec	VEMP (OEL TWAEV)	10 ppm
Saskatchewan	OEL STEL	15 ppm
Saskatchewan	OEL TWA	10 ppm
Yukon	OEL STEL	27 mg/m³
Yukon	OEL STEL	15 ppm
Yukon	OEL TWA	15 mg/m³
Yukon	OEL TWA	10 ppm

Carbon monoxide (630-08-0)		
ACGIH	ACGIH OEL TWA	25 ppm
OSHA	OSHA PEL TWA	55 mg/m³
OSHA	OSHA PEL TWA	50 ppm

Linde and the Linde wordmark are trademarks or registered trademarks of Linde plc or its affiliates. The information contained herein is offered for use by technically qualified personnel at their discretion and risk without warranty of any kind.

Copyright © 2024, Linde Inc.

Carbon monoxide (630-08-0)		
IDLH	IDLH	1200 ppm
NIOSH	NIOSH REL TWA	40 mg/m³
NIOSH	NIOSH REL TWA	35 ppm
NIOSH	NIOSH REL C	229 mg/m³
NIOSH	NIOSH REL C	200 ppm

Alberta	OEL TWA	29 mg/m³
Alberta	OEL TWA	25 ppm
British Columbia	OEL STEL	100 ppm
British Columbia	OEL TWA	25 ppm
Manitoba	OEL TWA	25 ppm
New Brunswick	OEL TWA	29 mg/m³
New Brunswick	OEL TWA	25 ppm
Newfoundland & Labrador	OEL TWA	25 ppm
Nova Scotia	OEL TWA	25 ppm
Nunavut	OEL STEL	460 mg/m³
Nunavut	OEL STEL	190 ppm
Nunavut	OEL TWA	57 mg/m³
Nunavut	OEL TWA	25 ppm
Northwest Territories	OEL STEL	190 ppm
Northwest Territories	OEL TWA	25 ppm
Ontario	OEL TWAEV	25 ppm
Prince Edward Island	OEL TWA	25 ppm
Québec	VECD (OEL STEV)	230 mg/m³
Québec	VECD (OEL STEV)	200 ppm
Québec	VEMP (OEL TWAEV)	40 mg/m³
Québec	VEMP (OEL TWAEV)	35 ppm
Saskatchewan	OEL STEL	190 ppm
Saskatchewan	OEL TWA	25 ppm
Yukon	OEL STEL	440 mg/m³
Yukon	OEL STEL	400 ppm
Yukon	OEL TWA	55 mg/m³
Yukon	OEL TWA	50 ppm

Nitrogen (7727-37-9)

Methane (74-82-8)

British Columbia	OEL TWA	1000 ppm
Nunavut	OEL STEL	1250 ppm
Nunavut	OEL TWA	1000 ppm
Northwest Territories	OEL STEL	1250 ppm
Northwest Territories	OEL TWA	1000 ppm
Saskatchewan	OEL STEL	1250 ppm

Linde and the Linde wordmark are trademarks or registered trademarks of Linde plc or its affiliates. The information contained herein is offered for use by technically qualified personnel at their discretion and risk without warranty of any kind.

Copyright © 2024, Linde Inc.

Saskatchewan	OEL TWA	1000 ppm

8.2. Exposure controls

Appropriate engineering controls : Provide adequate general and local exhaust ventilation. Ensure exposure is below occupational exposure limits (where available).

Personal protective equipment : Safety glasses. Gloves.



Eye protection : Wear safety glasses when handling cylinders; vapor-proof goggles and a face shield during cylinder changeout or whenever contact with product is possible. Select eye protection in accordance with OSHA 29 CFR 1910.133. Select in accordance with the current CSA standard Z94.3, "Industrial Eye and Face Protection", and any provincial regulations, local bylaws or guidelines.

Skin and body protection : Wear metatarsal shoes and work gloves for cylinder handling, and protective clothing where needed. Wear appropriate chemical gloves during cylinder changeout or wherever contact with product is possible. Select per OSHA 29 CFR 1910.132, 1910.136, and 1910.138. Safety shoes: Select in accordance with the current CSA standard Z195, "Protective Foot Wear", and any provincial regulations, local bylaws or guidelines.

Respiratory protection : When workplace conditions warrant respirator use, follow a respiratory protection program that meets OSHA 29 CFR 1910.134, ANSI Z88.2, or MSHA 30 CFR 72.710 (where applicable). Use an air-supplied or air-purifying cartridge if the action level is exceeded. Ensure that the respirator has the appropriate protection factor for the exposure level. If cartridge type respirators are used, the cartridge must be appropriate for the chemical exposure. For emergencies or instances with unknown exposure levels, use a self-contained breathing apparatus (SCBA).

Respiratory protection: Use respirable fume respirator or air supplied respirator when working in confined space or where local exhaust or ventilation does not keep exposure below OEL (if applicable). Select in accordance with provincial regulations, local bylaws or guidelines. Selection should be based on the current CSA standard Z94.4, "Selection, Care, and Use of Respirators." Respirators should also be approved by NIOSH and MSHA. For emergencies or instances with unknown exposure levels, use a self-contained breathing apparatus (SCBA).

Thermal hazard protection : Wear cold insulating gloves when transfilling or breaking transfer connections.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	:	Gas
Color	:	Colorless
Odor	:	No data available
Odor threshold	:	No data available
pH	:	Not applicable.
Relative evaporation rate (butyl acetate=1)	:	
Relative evaporation rate (ether=1)	:	Not applicable.
Melting point	:	No data available
Freezing point	:	No data available
Boiling point	:	No data available
Flash point	:	No data available
Relative evaporation rate (butyl acetate=1)	:	No data available
Relative evaporation rate (ether=1)	:	Not applicable.
Flammability	:	No data available
Explosion limits	:	No data available
Explosive properties	:	Not applicable.
Oxidizing properties	:	None.

Linde and the Linde wordmark are trademarks or registered trademarks of Linde plc or its affiliates. The information contained herein is offered for use by technically qualified personnel at their discretion and risk without warranty of any kind.

Copyright © 2024, Linde Inc.

Vapor pressure	:	Not applicable.
Relative density	:	No data available
Relative vapor density at 20°C	:	No data available
Solubility	:	Water: No data available
Partition coefficient n-octanol/water (Log Pow)	:	Not applicable.
Partition coefficient n-octanol/water (Log Kow)	:	Not applicable.
Auto-ignition temperature	:	No data available
Decomposition temperature	:	No data available
Viscosity	:	No data available
Viscosity, kinematic	:	Not applicable.
Viscosity, dynamic	:	Not applicable.

9.2. Other information

SECTION 10: Stability and reactivity

10.1. Reactivity

No reactivity hazard other than the effects described in sub-sections below.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

None.

10.4. Conditions to avoid

None.

10.5. Incompatible materials

None.

10.6. Hazardous decomposition products

None.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Likely routes of exposure	:	Inhalation
Acute toxicity	:	Not classified

Hydrogen sulfide (7783-06-4)	
LC50 Inhalation - Rat [ppm]	356 ppm/4h
ATE US (gases)	356 ppmV/4h

Carbon monoxide (630-08-0)	
LC50 Inhalation - Rat [ppm]	3760 ppm/1h
ATE US (gases)	1880 ppmV/4h

Skin corrosion/irritation	:	Not classified pH: Not applicable.
Serious eye damage/irritation	:	Not classified pH: Not applicable.
Respiratory or skin sensitization	:	Not classified
Germ cell mutagenicity	:	Not classified
Carcinogenicity	:	Not classified
Reproductive toxicity	:	Not classified
STOT-single exposure	:	Not classified

Linde and the Linde wordmark are trademarks or registered trademarks of Linde plc or its affiliates. The information contained herein is offered for use by technically qualified personnel at their discretion and risk without warranty of any kind.

Copyright © 2024, Linde Inc.

STOT-repeated exposure : Not classified

Aspiration hazard : Not applicable

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : No known ecological damage caused by this product.

Hydrogen sulfide (7783-06-4)	
LC50 - Fish [1]	0.0448 mg/l (Exposure time: 96 h - Species: Lepomis macrochirus [flow-through])
LC50 - Fish [2]	0.016 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])

12.2. Persistence and degradability

PTG-4001	
Persistence and degradability	No ecological damage caused by this product.

Hydrogen sulfide (7783-06-4)	
Persistence and degradability	Not applicable for inorganic gases.

Oxygen (7782-44-7)	
Persistence and degradability	No ecological damage caused by this product.

Nitrogen (7727-37-9)	
Persistence and degradability	No ecological damage caused by this product.

Methane (74-82-8)	
Persistence and degradability	The substance is biodegradable. Unlikely to persist.

12.3. Bioaccumulative potential

PTG-4001	
Partition coefficient n-octanol/water (Log Pow)	Not applicable.
Partition coefficient n-octanol/water (Log Kow)	Not applicable.
Bioaccumulative potential	No ecological damage caused by this product.

Hydrogen sulfide (7783-06-4)	
BCF - Fish [1]	(no bioaccumulation expected)
Partition coefficient n-octanol/water (Log Pow)	Not applicable.
Partition coefficient n-octanol/water (Log Kow)	Not applicable.
Bioaccumulative potential	No data available.

Carbon monoxide (630-08-0)	
Partition coefficient n-octanol/water (Log Kow)	Not applicable.

Oxygen (7782-44-7)	
Partition coefficient n-octanol/water (Log Pow)	Not applicable.
Partition coefficient n-octanol/water (Log Kow)	Not applicable.
Bioaccumulative potential	No ecological damage caused by this product.

Nitrogen (7727-37-9)	
Partition coefficient n-octanol/water (Log Pow)	Not applicable.
Partition coefficient n-octanol/water (Log Kow)	Not applicable.
Bioaccumulative potential	No ecological damage caused by this product.

Linde and the Linde wordmark are trademarks or registered trademarks of Linde plc or its affiliates. The information contained herein is offered for use by technically qualified personnel at their discretion and risk without warranty of any kind.

Copyright © 2024, Linde Inc.

Methane (74-82-8)	
Partition coefficient n-octanol/water (Log Pow)	1.09
Bioaccumulative potential	Not expected to bioaccumulate due to the low log Kow (log Kow < 4). Refer to section 9.

12.4. Mobility in soil

PTG-4001	
Mobility in soil	No data available.

Hydrogen sulfide (7783-06-4)	
Mobility in soil	No data available.
Ecology - soil	Because of its high volatility, the product is unlikely to cause ground or water pollution. Partition into soil is unlikely.

Carbon monoxide (630-08-0)	
Mobility in soil	No data available.

Oxygen (7782-44-7)	
Mobility in soil	No data available.
Ecology - soil	No ecological damage caused by this product.

Nitrogen (7727-37-9)	
Mobility in soil	No data available.
Ecology - soil	No ecological damage caused by this product.

Methane (74-82-8)	
Ecology - soil	Because of its high volatility, the product is unlikely to cause ground or water pollution.

12.5. Other adverse effects

Effect on ozone layer : None.

Effect on the global warming : Contains greenhouse gas(es) not covered by 842/2006/EC.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste treatment methods : Do not attempt to dispose of residual or unused quantities. Return container to supplier.

Product/Packaging disposal recommendations : Do not attempt to dispose of residual or unused quantities. Return container to supplier.

SECTION 14: Transport information

Department of Transportation (DOT)

In accordance with DOT

Transport document description (DOT) : UN1956 Compressed gas, n.o.s., 2.2

UN-No.(DOT) : UN1956

Proper Shipping Name (DOT) : Compressed gas, n.o.s.

Class (DOT) : 2.2 - Class 2.2 - Non-flammable compressed gas 49 CFR 173.115

Hazard labels (DOT) : 2.2 - Non-flammable gas



DOT Packaging Non Bulk (49 CFR 173.xxx) : 302;305

DOT Packaging Bulk (49 CFR 173.xxx) : 314;315

DOT Symbols : G - Identifies proper shipping name (PSN) requiring the addition of technical name(s) in parentheses following the PSN.

DOT Packaging Exceptions (49 CFR 173.xxx) : 306;307

Linde and the Linde wordmark are trademarks or registered trademarks of Linde plc or its affiliates. The information contained herein is offered for use by technically qualified personnel at their discretion and risk without warranty of any kind.

Copyright © 2024, Linde Inc.

DOT Quantity Limitations Passenger aircraft/rail (49 CFR 172.101 HMT, Column 9a)	:	75 kg
DOT Quantity Limitations Cargo aircraft only (49 CFR 172.101 HMT, Column 9b)	:	150 kg
DOT Vessel Stowage Location	:	A - The material may be stowed ‘‘on deck’’ or ‘‘under deck’’ on a cargo vessel and on a passenger vessel.

Additional information

Emergency Response Guide (ERG) Number	:	126
Other information	:	No supplementary information available.
Special transport precautions	:	Avoid transport on vehicles where the load space is not separated from the driver's compartment. Ensure vehicle driver is aware of the potential hazards of the load and knows what to do in the event of an accident or an emergency. Before transporting product containers: - Ensure there is adequate ventilation. - Ensure that containers are firmly secured. - Ensure cylinder valve is closed and not leaking. - Ensure valve outlet cap nut or plug (where provided) is correctly fitted. - Ensure valve protection device (where provided) is correctly fitted.

In accordance with TDG

Transportation of Dangerous Goods

UN-No. (TDG)	:	UN1956
Proper Shipping Name (TDG)	:	Compressed Gas, n.o.s.
TDG Primary Hazard Classes	:	2.2 - Class 2.2 - Non-Flammable, Non-Toxic Gases
Explosive Limit and Limited Quantity Index	:	0.125L
Passenger Carrying Road Vehicle or Passenger Carrying Railway Vehicle Index	:	75 L

Transport by sea

UN-No. (IMDG)	:	1956
Proper Shipping Name (IMDG)	:	COMPRESSED GAS, N.O.S.
Class (IMDG)	:	2 - Gases
Limited quantities (IMDG)	:	120ml
EmS-No. (1)	:	F-C
MFAG-No	:	620
EmS-No. (2)	:	S-V

Air transport

UN-No. (IATA)	:	1956
Proper Shipping Name (IATA)	:	Compressed gas, n.o.s.
Class (IATA)	:	2 - Gases
Instruction "cargo" (ICAO)	:	200
Instruction "passenger" (ICAO)	:	200
Instruction "passenger" - Limited quantities (ICAO)	:	FORBIDDEN
Civil Aeronautics Law	:	Gases under pressure/Gases nonflammable nontoxic under pressure

SECTION 15: Regulatory information

15.1. US Federal regulations

Linde and the Linde wordmark are trademarks or registered trademarks of Linde plc or its affiliates. The information contained herein is offered for use by technically qualified personnel at their discretion and risk without warranty of any kind.

Copyright © 2024, Linde Inc.

PTG-4001
Listed on the United States SARA Section 302 Subject to reporting requirements of United States SARA Section 313 Listed on the United States TSCA (Toxic Substances Control Act) inventory

Hydrogen sulfide (7783-06-4)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory Listed on the United States SARA Section 302 Subject to reporting requirements of United States SARA Section 313	
SARA Section 302 Threshold Planning Quantity (TPQ)	500 lb
SARA Section 313 - Emission Reporting	1 %

Carbon monoxide (630-08-0)
Listed on the United States TSCA (Toxic Substances Control Act) inventory

Oxygen (7782-44-7)
Listed on the United States TSCA (Toxic Substances Control Act) inventory

Nitrogen (7727-37-9)
Listed on the United States TSCA (Toxic Substances Control Act) inventory

Methane (74-82-8)
Listed on the United States TSCA (Toxic Substances Control Act) inventory

15.2. International regulations

CANADA

PTG-4001	
Listed on the Canadian DSL (Domestic Substances List)	
WHMIS Classification	Class A - Compressed Gas

Hydrogen sulfide (7783-06-4)	
Listed on the Canadian DSL (Domestic Substances List)	
WHMIS Classification	Class A - Compressed Gas Class B Division 1 - Flammable Gas Class D Division 1 Subdivision A - Very toxic material causing immediate and serious toxic effects Class D Division 2 Subdivision B - Toxic material causing other toxic effects

Carbon monoxide (630-08-0)	
Listed on the Canadian DSL (Domestic Substances List)	
WHMIS Classification	Class A - Compressed Gas Class B Division 1 - Flammable Gas Class D Division 1 Subdivision A - Very toxic material causing immediate and serious toxic effects Class D Division 2 Subdivision A - Very toxic material causing other toxic effects

Oxygen (7782-44-7)	
Listed on the Canadian DSL (Domestic Substances List)	
WHMIS Classification	Class A - Compressed Gas Class C - Oxidizing Material

Nitrogen (7727-37-9)	
Listed on the Canadian DSL (Domestic Substances List)	
WHMIS Classification	Class A - Compressed Gas

Methane (74-82-8)	
Listed on the Canadian DSL (Domestic Substances List)	
WHMIS Classification	Class A - Compressed Gas Class B Division 1 - Flammable Gas

EU-Regulations

Linde and the Linde wordmark are trademarks or registered trademarks of Linde plc or its affiliates. The information contained herein is offered for use by technically qualified personnel at their discretion and risk without warranty of any kind.

Copyright © 2024, Linde Inc.

Hydrogen sulfide (7783-06-4)
Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

Carbon monoxide (630-08-0)
Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

Oxygen (7782-44-7)
Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

Nitrogen (7727-37-9)
Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

Methane (74-82-8)
Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

Classification according to Regulation (EC) No. 1272/2008 [CLP]
Press. Gas (Comp.) H280

Classification according to Directive 67/548/EEC [DSD] or 1999/45/EC [DPD]
No additional information available

National regulations

Hydrogen sulfide (7783-06-4)
Listed introduction on Australian Industrial Chemicals Introduction Scheme (AICIS Inventory) Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China) Listed on the Japanese ENCS (Existing New Chemical Substances) inventory Listed on the Japanese ISHL (Industrial Safety and Health Law) Listed on KECL/KECI (Korean Existing Chemicals Inventory) Listed on NZIoC (New Zealand Inventory of Chemicals) Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances) Listed on the Canadian IDL (Ingredient Disclosure List) Listed on INSQ (Mexican National Inventory of Chemical Substances) Listed on the TCSI (Taiwan Chemical Substance Inventory)

Carbon monoxide (630-08-0)
Listed introduction on Australian Industrial Chemicals Introduction Scheme (AICIS Inventory) Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China) Listed on the Japanese ENCS (Existing New Chemical Substances) inventory Listed on the Japanese ISHL (Industrial Safety and Health Law) Listed on KECL/KECI (Korean Existing Chemicals Inventory) Listed on NZIoC (New Zealand Inventory of Chemicals) Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances) Listed on the Canadian IDL (Ingredient Disclosure List) Listed on INSQ (Mexican National Inventory of Chemical Substances) Listed on the TCSI (Taiwan Chemical Substance Inventory)

Oxygen (7782-44-7)
Listed introduction on Australian Industrial Chemicals Introduction Scheme (AICIS Inventory) Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China) Listed on KECL/KECI (Korean Existing Chemicals Inventory) Listed on NZIoC (New Zealand Inventory of Chemicals) Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances) Listed on INSQ (Mexican National Inventory of Chemical Substances) Listed on the TCSI (Taiwan Chemical Substance Inventory)

Nitrogen (7727-37-9)
Listed introduction on Australian Industrial Chemicals Introduction Scheme (AICIS Inventory) Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China) Listed on KECL/KECI (Korean Existing Chemicals Inventory) Listed on NZIoC (New Zealand Inventory of Chemicals) Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances) Listed on INSQ (Mexican National Inventory of Chemical Substances)

Linde and the Linde wordmark are trademarks or registered trademarks of Linde plc or its affiliates. The information contained herein is offered for use by technically qualified personnel at their discretion and risk without warranty of any kind.

Copyright © 2024, Linde Inc.

Methane (74-82-8)
Listed introduction on Australian Industrial Chemicals Introduction Scheme (AICIS Inventory) Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China) Listed on the Japanese ENCS (Existing New Chemical Substances) inventory Listed on KECL/KECI (Korean Existing Chemicals Inventory) Listed on NZIoC (New Zealand Inventory of Chemicals) Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances) Listed on INSQ (Mexican National Inventory of Chemical Substances) Listed on CICR (Turkish Inventory and Control of Chemicals)

15.3. US State regulations

PTG-4001()	
U.S. - California - Proposition 65 - Carcinogens List	No
U.S. - California - Proposition 65 - Developmental Toxicity	Yes
U.S. - California - Proposition 65 - Reproductive Toxicity - Female	No
U.S. - California - Proposition 65 - Reproductive Toxicity - Male	No

Carbon monoxide (630-08-0)				
U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	No significant risk level (NSRL)
No	Yes	No	No	

Hydrogen sulfide (7783-06-4)
U.S. - Massachusetts - Right To Know List U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List U.S. - Pennsylvania - RTK (Right to Know) List

Carbon monoxide (630-08-0)
U.S. - Massachusetts - Right To Know List U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List U.S. - Pennsylvania - RTK (Right to Know) List

Oxygen (7782-44-7)
U.S. - Massachusetts - Right To Know List U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - Pennsylvania - RTK (Right to Know) List

Nitrogen (7727-37-9)
U.S. - Massachusetts - Right To Know List U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - Pennsylvania - RTK (Right to Know) List

Methane (74-82-8)
U.S. - Massachusetts - Right To Know List U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - Pennsylvania - RTK (Right to Know) List

SECTION 16: Other information

Revision date : 05/17/2024

Linde and the Linde wordmark are trademarks or registered trademarks of Linde plc or its affiliates. The information contained herein is offered for use by technically qualified personnel at their discretion and risk without warranty of any kind.

Copyright © 2024, Linde Inc.

Other information	:	When you mix two or more chemicals, you can create additional, unexpected hazards. Obtain and evaluate the safety information for each component before you produce the mixture. Consult an industrial hygienist or other trained person when you evaluate the end product. Before using any plastics, confirm their compatibility with this product. Linde asks users of this product to study this SDS and become aware of the product hazards and safety information. To promote safe use of this product, a user should (1) notify employees, agents, and contractors of the information in this SDS and of any other known product hazards and safety information, (2) furnish this information to each purchaser of the product, and (3) ask each purchaser to notify its employees and customers of the product hazards and safety information. The opinions expressed herein are those of qualified experts within Linde Inc. We believe that the information contained herein is current as of the date of this Safety Data Sheet. Since the use of this information and the conditions of use are not within the control of Linde Inc, it is the user's obligation to determine the conditions of safe use of the product. Linde SDSs are furnished on sale or delivery by Linde or the independent distributors and suppliers who package and sell our products. To obtain current SDSs for these products, contact your sales representative, local distributor, or supplier, or download from www.lindeus.com. Linde and the Linde wordmark are trademarks or registered trademarks of Linde plc or its affiliates. The information contained herein is offered for use by technically qualified personnel at their discretion and risk without warranty of any kind. Copyright © 2024, Linde Inc.

SDS US_and_Canada

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.

Linde and the Linde wordmark are trademarks or registered trademarks of Linde plc or its affiliates. The information contained herein is offered for use by technically qualified personnel at their discretion and risk without warranty of any kind.

Copyright © 2024, Linde Inc.

PTG-4001

Fiche de Données de Sécurité PTG-4001

conforme Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations
conformément à la Loi sur les produits dangereux (11 février 2015).

Date d'émission: 05/05/2015 Date de révision: 05/17/2024 Remplace la fiche: 02/21/2022 Version: 1.4

SECTION 1: Identification

1.1. Identificateur de produit

Forme du produit : Mélange

Nom du produit : PTG-4001

Formule brute : (0.00001 - 0.9999 %) Hydrogen Sulfide, (0.0001 - 0.0999 %) Carbon Monoxide, (0.0001 - 3.5 %) Methane, (0.0001 - 19.5 %) Oxygen in Nitrogen.

1.2. Utilisations identifiées pertinentes de la substance ou du mélange et utilisations déconseillées

Utilisation de la substance/mélange : Utilisation industrielle; Utiliser conformément aux instructions.

Usage recommandé et restrictions d'utilisation : Calibration / Reference

1.3. Renseignements concernant le fournisseur de la fiche de données de sécurité

USA:
PortaGas, a Linde Company
(Linde Gas & Equipment LLC.),
1202 E Sam Houston Pkwy S
Pasadena, TX 77503
T +1 713-928-6477 - F +1 713-928-9961
PDImsds@Praxair.com

Canada:
Linde Canada
5015 Spectrum Way, Suite 500
Mississauga, Ontario, L4W 0E4
1-800-225-8247

1.4. Numéro d'appel d'urgence

Numéro d'urgence : Urgence: 1-800-645-4633
CHEMTREC 24 h / jour 7 jours / semaine
- Aux États-Unis: 1-800-424-9300, à l'extérieur des États-Unis: 001-703-527-3887
(appels à frais virés acceptés, 17729)

SECTION 2: Identification des dangers

2.1. Classification de la substance ou du mélange

Classification SGH-US

Press. Gas (Comp.) H280
Simple asphyxiant SIAS

2.2. Éléments d'étiquetage

Étiquetage GHS US

Pictogrammes de danger (GHS-US) :



GHS04

Mot-indicateur (GHS US) : Attention

Mentions de danger (GHS US) : H280 - CONTIENT UN GAZ SOUS PRESSION; PEUT EXPLOSER SOUS L'EFFET DE LA CHALEUR
OSHA-H01 - PEUT DÉPLACER L'OXYGÈNE ET ENTRAÎNER SUFFOCATION RAPIDE.

Conseils de prudence (GHS US) : P403 - Utiliser seulement en plein air ou dans un endroit bien ventilé.
CGA-PG21 - Ouvrir le robinet lentement.
CGA-PG12 - Ne pas ouvrir le robinet tant et aussi longtemps qu'il n'est pas raccordé au matériel prêt à l'utilisation.
CGA-PG11 - Ne jamais mettre les bouteilles dans des endroits non aérés où des véhicules circulent.
CGA-PG10 - Utiliser uniquement avec du matériel prévu pour la pression de la bouteille.
CGA-PG06 - Fermer le robinet après chaque utilisation et lorsque la bouteille de gaz est vide.
CGA-PG05 - Installer un antiretour dans les tuyaux.
CGA-PG02 - Protéger des rayons solaires lorsque la température ambiante est supérieure à 52 °C (125 °F).

Linde es un marque commerciale ou un marque déposées de Linde Inc. aux États-Unis et/ou dans d'autres pays.

2.3. Autres dangers

2.4. Unknown acute toxicity (GHS US)

SECTION 2: Identification des dangers

2.1. Classification de la substance ou du mélange

Classification (GHS CA)

Gaz sous pression Gaz comprimé H280

2.2. Éléments d'étiquetage SGH, y compris conseils de prudence

Étiquetage GHS CA

Pictogrammes de danger :



GHS04

Mot-indicateur : Attention

Mentions de danger : CONTIENT UN GAZ SOUS PRESSION; PEUT EXPLOSER SOUS L'EFFET DE LA CHALEUR

Conseils de prudence : Utiliser seulement en plein air ou dans un endroit bien ventilé.
Ouvrir le robinet lentement.
Ne pas ouvrir le robinet tant et aussi longtemps qu'il n'est pas raccordé au matériel prêt à l'utilisation.
Ne jamais mettre les bouteilles dans des endroits non aérés où des véhicules circulent.
Utiliser uniquement avec du matériel prévu pour la pression de la bouteille.
Fermer le robinet après chaque utilisation et lorsque la bouteille de gaz est vide.
Installer un antiretour dans les tuyaux.
Protéger des rayons solaires lorsque la température ambiante est supérieure à 52 °C (125 °F).

2.3. Autres dangers

2.4. Toxicité aiguë inconnue (GHS CA)

SECTION 3: Composition/information sur les ingrédients

3.1. Substances

Sans objet

3.2. Mélanges

Nom	Identificateur de produit	%	Nom commun (synonymes)
Nitrogen	(N° CAS) 7727-37-9	75.9002 – 100	Nitrogen gas / NITROGEN / Nitrogen, compressed
Oxygène	(N° CAS) 7782-44-7	0.0001 – 19.5	Oxygen (dissolved) / Oxygen gas / Oxygen, compressed / Oxygen, dissolved
Méthane	(N° CAS) 74-82-8	0.0001 – 3.5	Marsh gas / Natural gas, refrigerated liquid / Methane, compressed
Sulfure d'hydrogène	(N° CAS) 7783-06-4	0.0001 – 1	Hydrogen sulfide (H2S) / Hydrogen sulphide / Sulfur hydride / Sulfureted hydrogen / Dihydrogen sulphide / Hydrogensulfide
Monoxyde de carbone	(N° CAS) 630-08-0	0.0001 – 0.0999	Carbon monoxide, compressed / Compressed carbon monoxide / Carbon oxide (CO) / Carbon(II) oxide / Carbon oxide

Nom	Identificateur de produit	%	Nom commun (synonymes)
Nitrogen	(N° CAS) 7727-37-9	75.9002 – 100	Nitrogen gas / NITROGEN / Nitrogen, compressed

Linde es un marque commerciale ou un marque déposées de Linde Inc. aux États-Unis et/ou dans d'autres pays.

Nom	Identificateur de produit	%	Nom commun (synonymes)
Oxygène	(N° CAS) 7782-44-7	0.0001 – 19.5	Oxygen (dissolved) / Oxygen gas / Oxygen, compressed / Oxygen, dissolved
Méthane	(N° CAS) 74-82-8	0.0001 – 3.5	Marsh gas / Natural gas, refrigerated liquid / Methane, compressed
Sulfure d'hydrogène	(N° CAS) 7783-06-4	0.0001 – 1	Hydrogen sulfide (H2S) / Hydrogen sulphide / Sulfur hydride / Sulfureted hydrogen / Dihydrogen sulphide / Hydrogensulfide
Monoxyde de carbone	(N° CAS) 630-08-0	0.0001 – 0.0999	Carbon monoxide, compressed / Compressed carbon monoxide / Carbon oxide (CO) / Carbon(II) oxide / Carbon oxide

Sulfure d'hydrogène (7783-06-4)	
Classification SIMDUT	Catégorie A – Gaz comprimés Catégorie B – Division 1 : Gaz inflammable Catégorie D – Division 1, Sous-division A : Matière très toxique Catégorie D –Division 2, Sous-division B : Matière toxique

Monoxyde de carbone (630-08-0)	
Classification SIMDUT	Catégorie A – Gaz comprimés Catégorie B – Division 1 : Gaz inflammable Catégorie D – Division 1, Sous-division A : Matière très toxique Catégorie D – Division 2, Sous-division A : Matière très toxique

Oxygène (7782-44-7)	
Classification SIMDUT	Catégorie A – Gaz comprimés Catégorie C – Matières comburantes

Nitrogen (7727-37-9)	
Classification SIMDUT	Catégorie A – Gaz comprimés

Méthane (74-82-8)	
Classification SIMDUT	Catégorie A – Gaz comprimés Catégorie B – Division 1 : Gaz inflammable

SECTION 4: Premiers secours

4.1. Description des mesures de premiers secours

Premiers soins après inhalation : Transporter la victime à l'extérieur et la maintenir au repos dans une position où elle peut confortablement respirer. En cas d'arrêt de la respiration, donner la respiration artificielle. Si la respiration est difficile, le personnel qualifié peut administrer de l'oxygène. Appeler un médecin.

Premiers soins après contact avec la peau : Pas d'effets néfastes attendus avec ce produit.

Premiers soins après contact oculaire : Rincer immédiatement et abondamment les yeux avec de l'eau pendant au moins 15 minutes. Tenir les paupières ouvertes et loin des yeux afin d'assurer que toutes les surfaces sont rincées à fond. Consulter immédiatement un ophtalmologiste.

Premiers soins après ingestion : L'ingestion n'est pas considérée comme une voie d'exposition possible.

4.2. Principaux symptômes et effets, aigus et différés

Symptômes/effets : Les effets sont causés par un manque d'oxygène. Des concentrations modérées peuvent causer des maux de tête, de la somnolence, des étourdissements, des vertiges, de l'excitation, une salivation excessive, des vomissements et des évanouissements. L'exposition prolongée à des concentrations faibles de monoxyde de carbone peut entrainer la mort. Inhalation.

4.3. Indication des éventuels soins médicaux immédiats et traitements particuliers nécessaires

None.

SECTION 5: Mesures de lutte contre l'incendie

5.1. Moyens d'extinction

Moyens d'extinction appropriés : Utiliser les moyens adéquats pour circonscrire l'incendie.

5.2. Dangers particuliers résultant de la substance ou du mélange

Risque d'incendie : Non inflammable.

Danger d'explosion : La chaleur peut provoquer une pressurisation et l'éclatement des conteneurs clos, propageant le feu et augmentant le risque de brûlures/blessures.

Réactivité : Pas de danger de réactivité autre que les effets décrits dans les sections ci-dessous.

Linde es un marque commerciale ou un marque déposées de Linde Inc. aux États-Unis et/ou dans d'autres pays.

5.3. Conseils aux pompiers

Instructions de lutte contre l'incendie	:	Évacuer tout le personnel de la zone dangereuse. Utiliser un appareil respiratoire autonome et des vêtements de protection. Refroidir immédiatement les contenants avec de l'eau à une distance maximale. Arrêter l'écoulement de gaz si cela peut être fait de manière sécuritaire, tout en continuant de pulvériser de l'eau. Éliminer les sources d'ignition si cela peut être fait de manière sécuritaire. Enlever les contenants de la zone d'incendie si cela peut être fait de manière sécuritaire. Les pompiers sur place doivent se conformer aux règlements des codes d'incendie provincial et local.
Équipements de protection spéciaux pour pompiers	:	Vêtement de protection et équipement de respiration autonome destinés aux pompiers.
Autres informations	:	Les contenants sont équipés d'un détendeur de pression (il peut y avoir des exceptions autorisées par TC).

SECTION 6: Mesures à prendre en cas de déversement accidentel

6.1. Précautions individuelles, équipement de protection et procédures d'urgence

6.1.1. Pour les non-secouristes

Procédures d'urgence : Eloigner le personnel superflu.

6.1.2. Pour les secouristes

6.2. Précautions pour la protection de l'environnement

Empêcher les résidus de contaminer les environs.

6.3. Méthodes et matériel de confinement et de nettoyage

6.4. Référence à d'autres rubriques

Voir aussi les sections 8 et 13.

SECTION 7: Manutention et stockage

7.1. Précautions à prendre pour une manipulation sans danger

Précautions à prendre pour une manipulation sans danger	:	Porter des gants de protection en cuir pour manipuler les bouteilles. Protéger les bouteilles contre tout dommage. Ne pas traîner, faire rouler, faire glisser ni laisser tomber les bouteilles. Toujours garder le chapeau du robinet en place quand on déplace une bouteille. Ne jamais soulever une bouteille par son chapeau; le chapeau est conçu uniquement pour protéger le robinet. Utiliser un chariot porte-bouteille pour déplacer les bouteilles, même sur une courte distance. Ne jamais insérer un objet (par exemple, une clé, un tournevis, un levier) dans les ouvertures du chapeau; cela pourrait endommager le robinet et provoquer une fuite. Utiliser une clé à courroie pour enlever les chapeaux trop serrés ou rouillés. Ouvrir lentement le robinet. Si le robinet est difficile à ouvrir, arrêter l'utilisation et contacter votre fournisseur. Fermer le robinet du contenant après chaque utilisation; garder le robinet fermé même quand ce contenant est vide. Ne jamais appliquer une flamme ou de la chaleur localisée directement sur une quelconque partie du contenant. Les températures élevées peuvent endommager le contenant et causer une défaillance prématurée du détendeur de pression du contenant et en vider le contenu. Pour les autres précautions d'utilisation de ce produit, voir la section 16.

7.2. Conditions d'un stockage sûr, y compris les éventuelles incompatibilités

Mesures techniques : Se conformer aux réglementations en vigueur.

Conditions de stockage	:	Conserver dans un endroit frais et bien ventilé. Stocker et utiliser avec une ventilation adéquate. Stocker uniquement dans un endroit où la température ne dépassera pas 52 ºC (125 ºF). Fixer fermement les récipients en position verticale pour éviter qu'ils ne tombent ou ne soient renversés. Installer fermement à la main le capuchon de protection de la valve. Stocker séparément les récipients pleins et les récipients vides. Utiliser un système d'inventaire « premier entré, premier sorti » pour éviter de stocker des récipients pleins pendant de longues périodes. **AUTRES PRÉCAUTIONS POUR LA MANUTENTION, STOCKAGE ET UTILISATION:** Lors de la manipulation du produit sous pression, utiliser la tuyauterie et l'équipement conçus pour supporter les pressions auxquelles on sera en présence. Ne jamais travailler sur un système sous pression. Utiliser un antiretour dans la tuyauterie. Les gaz peuvent causer une suffocation rapide en raison d'un manque d'oxygène; les stocker et les utiliser avec une ventilation adéquate. Si une fuite se produit, fermer le robinet du réservoir et purger le système d'une manière sûre et écologiquement correct en conformité avec toutes les lois internationales, fédérales / nationales, étatiques / provinciales et locales; réparer ensuite la fuite. Ne jamais placer un contenant où il peut faire partie d'un circuit électrique.

7.3. Utilisation(s) finale(s) particulière(s)

None.

SECTION 8: Contrôles de l'exposition/protection individuelle

8.1. Paramètres de contrôle

PTG-4001	
ACGIH	Sans objet
OSHA	Sans objet

Sulfure d'hydrogène (7783-06-4)		
ACGIH	ACGIH OEL TWA	1 ppm
ACGIH	ACGIH OEL STEL	5 ppm
OSHA	OSHA PEL C	20 ppm

Monoxyde de carbone (630-08-0)		
ACGIH	ACGIH OEL TWA	25 ppm
OSHA	OSHA PEL TWA	55 mg/m³
OSHA	OSHA PEL TWA	50 ppm

Oxygène (7782-44-7)	
ACGIH	Sans objet
OSHA	Sans objet

Nitrogen (7727-37-9)	
ACGIH	Sans objet
OSHA	Sans objet

Méthane (74-82-8)	
ACGIH	Sans objet
OSHA	Sans objet

Sulfure d'hydrogène (7783-06-4)		
ACGIH	ACGIH OEL TWA	1 ppm
ACGIH	ACGIH OEL STEL	5 ppm
OSHA	OSHA PEL C	20 ppm
IDLH	IDLH	100 ppm
NIOSH	NIOSH REL C	15 mg/m³

Sulfure d'hydrogène (7783-06-4)		
NIOSH	NIOSH REL C	10 ppm

Alberta	LEMT C	21 mg/m³
Alberta	LEMT C	15 ppm
Alberta	LEMT TWA	14 mg/m³
Alberta	LEMT TWA	10 ppm
Colombie-Britannique	LEMT C	10 ppm
Manitoba	LEMT STEL	5 ppm
Manitoba	LEMT TWA	1 ppm
Nouveau-Brunswick	LEMT STEL	21 mg/m³
Nouveau-Brunswick	LEMT STEL	15 ppm
Nouveau-Brunswick	LEMT TWA	14 mg/m³
Nouveau-Brunswick	LEMT TWA	10 ppm
Terre-Neuve-et-Labrador	LEMT STEL	5 ppm
Terre-Neuve-et-Labrador	LEMT TWA	1 ppm
Nouvelle-Écosse	LEMT STEL	5 ppm
Nouvelle-Écosse	LEMT TWA	1 ppm
Nunavut	LEMT C	28 mg/m³
Nunavut	LEMT C	20 ppm
Nunavut	LEMT STEL	21 mg/m³
Nunavut	LEMT STEL	15 ppm
Nunavut	LEMT TWA	14 mg/m³
Nunavut	LEMT TWA	10 ppm
Territoires du Nord-Ouest	LEMT STEL	15 ppm
Territoires du Nord-Ouest	LEMT TWA	10 ppm
Ontario	LEMT LMPT	15 ppm
Ontario	LEMT LMPT	10 ppm
Île-du-Prince-Édouard	LEMT STEL	5 ppm
Île-du-Prince-Édouard	LEMT TWA	1 ppm
Québec	VECD	21 mg/m³
Québec	VECD	15 ppm
Québec	VEMP	14 mg/m³
Québec	VEMP	10 ppm
Saskatchewan	LEMT STEL	15 ppm
Saskatchewan	LEMT TWA	10 ppm
Yukon	LEMT STEL	27 mg/m³
Yukon	LEMT STEL	15 ppm
Yukon	LEMT TWA	15 mg/m³
Yukon	LEMT TWA	10 ppm

Monoxyde de carbone (630-08-0)		
ACGIH	ACGIH OEL TWA	25 ppm
OSHA	OSHA PEL TWA	55 mg/m³
OSHA	OSHA PEL TWA	50 ppm
IDLH	IDLH	1200 ppm
NIOSH	NIOSH REL TWA	40 mg/m³

Monoxyde de carbone (630-08-0)		
NIOSH	NIOSH REL TWA	35 ppm
NIOSH	NIOSH REL C	229 mg/m³
NIOSH	NIOSH REL C	200 ppm

Alberta	LEMT TWA	29 mg/m³
Alberta	LEMT TWA	25 ppm
Colombie-Britannique	LEMT STEL	100 ppm
Colombie-Britannique	LEMT TWA	25 ppm
Manitoba	LEMT TWA	25 ppm
Nouveau-Brunswick	LEMT TWA	29 mg/m³
Nouveau-Brunswick	LEMT TWA	25 ppm
Terre-Neuve-et-Labrador	LEMT TWA	25 ppm
Nouvelle-Écosse	LEMT TWA	25 ppm
Nunavut	LEMT STEL	460 mg/m³
Nunavut	LEMT STEL	190 ppm
Nunavut	LEMT TWA	57 mg/m³
Nunavut	LEMT TWA	25 ppm
Territoires du Nord-Ouest	LEMT STEL	190 ppm
Territoires du Nord-Ouest	LEMT TWA	25 ppm
Ontario	LEMT LMPT	25 ppm
Île-du-Prince-Édouard	LEMT TWA	25 ppm
Québec	VECD	230 mg/m³
Québec	VECD	200 ppm
Québec	VEMP	40 mg/m³
Québec	VEMP	35 ppm
Saskatchewan	LEMT STEL	190 ppm
Saskatchewan	LEMT TWA	25 ppm
Yukon	LEMT STEL	440 mg/m³
Yukon	LEMT STEL	400 ppm
Yukon	LEMT TWA	55 mg/m³
Yukon	LEMT TWA	50 ppm

Nitrogen (7727-37-9)

Méthane (74-82-8)

Colombie-Britannique	LEMT TWA	1000 ppm
Nunavut	LEMT STEL	1250 ppm
Nunavut	LEMT TWA	1000 ppm
Territoires du Nord-Ouest	LEMT STEL	1250 ppm
Territoires du Nord-Ouest	LEMT TWA	1000 ppm
Saskatchewan	LEMT STEL	1250 ppm
Saskatchewan	LEMT TWA	1000 ppm

8.2. Contrôles de l'exposition

Contrôles techniques appropriés : Prévoir une extraction locale et générale adéquate. S'assurer que les limites d'exposition ne sont pas dépassées.

Équipement de protection individuelle	:	Lunettes de sécurité. Des gants. 
Protection oculaire	:	Porter des lunettes de sécurité lors de la manipulation des cylindres; des lunettes étanches à la vapeur un écran facial pendant le remplacement des de cylindre ou chaque fois que le contact avec le produit est possible. Choisir en conformité avec la norme CSA Z94.3,courante «Protecteurs oculaires et faciaux pour l'industrie », et les directives et règlements provinciaux. Les choisir en conformité avec la norme CSA Z94.3 courante, **«Protecteurs oculaires et faciaux pour l'industrie»**, et tous les règlements provinciaux.
Protection de la peau et du corps	:	Porter des chaussures à support métatarsien et des gants de travail pour la manutention des bouteilles, ainsi que des vêtements de protection en cas de besoin. Porter des gants résistants aux produits chimiques lors du remplacement des bouteilles, ou quand il y a possibilité de contact avec le produit. . Chaussures de sécurité: Choisir en conformité avec la norme courante Z195 de la CSA, « Chaussures de protection », et avec les directives et règlements locaux ou provinciaux en vigueur.
Protection des voies respiratoires	:	Lorsque les conditions de travail exigent l'utilisation d'un respirateur, suivre un programme de protection respiratoire qui conforme à la norme CSA Z94.4 courante, «Choix, entretien et utilisation des appareils respiratoires». Respirateurs doit également être approuvé par le NIOSH et MSHA. L'utilisation d'une cartouche d'air fourni ou de purification d'air si le niveau d'intervention est dépassé. Assurez-vous que le respirateur a le facteur de protection approprié pour le niveau d'exposition. Si des respirateurs de type de cartouche sont utilisés, la cartouche doit être approprié pour l'exposition aux produits chimiques. Cas d'urgence ou d'exposition à des niveaux inconnus, utiliser un appareil respiratoire autonome (ARA). **Protection respiratoire :** Porter un respirateur à adduction d'air pour les travaux dans des espaces clos ou dans des endroits où le système de ventilation ou l'aération ne sont pas suffisants pour garder le taux d'exposition sous le seuil admissible d'exposition (le cas échéant). Le choisir en conformité avec la réglementation provinciale, les règlements municipaux ou des lignes directrices en la matière. Les appareils respiratoires doivent être approuvés par le NIOSH et la MSHA. En cas d'urgence ou de niveaux d'exposition inconnus, utiliser un appareil respiratoire autonome (ARA).
Protection contre les dangers thermiques	:	Porter des gants isolant du froid lors d'opérations de transvasement ou de débranchement des conduites et raccords.

SECTION 9: Propriétés physiques et chimiques

9.1. Informations sur les propriétés physiques et chimiques essentielles

État physique	:	Gaz
Couleur	:	Incolore
Odeur	:	Aucune donnée disponible
Seuil olfactif	:	Aucune donnée disponible
pH	:	Sans objet.
Vitesse d'évaporation relative (acétate de butyle=1)	:	
Vitesse d'évaporation relative (éther=1)	:	Sans objet.
Point de fusion	:	Aucune donnée disponible
Point de congélation	:	Aucune donnée disponible
Point d'ébullition	:	Aucune donnée disponible
Point d'éclair	:	Aucune donnée disponible
Vitesse d'évaporation relative (acétate de butyle=1)	:	Aucune donnée disponible
Vitesse d'évaporation relative (éther=1)	:	Sans objet.
Inflammabilité	:	Aucune donnée disponible
Limites d'explosivité	:	Aucune donnée disponible
Propriétés explosives	:	Sans objet.
Propriétés comburantes	:	None.
Pression de la vapeur	:	Sans objet.

Densité relative	:	Aucune donnée disponible
Densité relative de la vapeur à 20°C	:	Aucune donnée disponible
Solubilité	:	Eau: Aucune donnée disponible
Coefficient de partage n-octanol/eau (Log Pow)	:	Sans objet.
Coefficient de partage n-octanol/eau (Log Kow)	:	Sans objet.
Température d'auto-inflammation	:	Aucune donnée disponible
Température de décomposition	:	Aucune donnée disponible
Viscosité	:	Aucune donnée disponible
Viscosité, cinématique	:	Sans objet.
Viscosité, dynamique	:	Sans objet.

9.2. Autres informations

SECTION 10: Stabilité et réactivité

10.1. Réactivité

Pas de danger de réactivité autre que les effets décrits dans les sections ci-dessous.

10.2. Stabilité chimique

Stable dans les conditions normales.

10.3. Possibilité de réactions dangereuses

None.

10.4. Conditions à éviter

None.

10.5. Matières incompatibles

None.

10.6. Produits de décomposition dangereux

None.

SECTION 11: Données toxicologiques

11.1. Informations sur les effets toxicologiques

Voies d'exposition possibles	:	Inhalation
Toxicité aiguë	:	non classé

Sulfure d'hydrogène (7783-06-4)	
CL50 Inhalation - Rat [ppm]	356 ppm/4h
ATE US (gaz)	356 ppmv/4h

Monoxyde de carbone (630-08-0)	
CL50 Inhalation - Rat [ppm]	3760 ppm/1h
ATE US (gaz)	1880 ppmv/4h

Corrosion cutanée/irritation cutanée	:	non classé pH: Sans objet.
Lésions oculaires graves/irritation oculaire	:	non classé pH: Sans objet.
Sensibilisation respiratoire ou cutanée	:	non classé
Mutagénicité sur les cellules germinales	:	non classé
Cancérogénicité	:	non classé
Toxicité pour la reproduction	:	non classé
Toxicité spécifique pour certains organes cibles (STOT) (exposition unique)	:	non classé

Linde es un marque commerciale ou un marque déposées de Linde Inc. aux États-Unis et/ou dans d'autres pays.

Toxicité spécifique pour certains organes cibles (STOT) (exposition répétée) : non classé

Danger par aspiration : Sans objet

SECTION 12: Données écologiques

12.1. Toxicité

Écologie - général : Pas d'effet écologique connu causé par ce produit.

Sulfure d'hydrogène (7783-06-4)	
CL50 - Poissons [1]	0.0448 mg/l (Exposure time: 96 h - Species: Lepomis macrochirus [flow-through])
CL50 - Poissons [2]	0.016 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])

12.2. Persistance et dégradabilité

PTG-4001	
Persistance et dégradabilité	Ce produit est sans risque sur le plan écologique.

Sulfure d'hydrogène (7783-06-4)	
Persistance et dégradabilité	Non applicable aux gaz non organiques..

Oxygène (7782-44-7)	
Persistance et dégradabilité	Ce produit est sans risque sur le plan écologique.

Nitrogen (7727-37-9)	
Persistance et dégradabilité	Ce produit est sans risque sur le plan écologique.

Méthane (74-82-8)	
Persistance et dégradabilité	Substance biodégradable. Persistance improbable.

12.3. Potentiel de bioaccumulation

PTG-4001	
Coefficient de partage n-octanol/eau (Log Pow)	Sans objet.
Coefficient de partage n-octanol/eau (Log Kow)	Sans objet.
Potentiel de bioaccumulation	Ce produit est sans risque sur le plan écologique.

Sulfure d'hydrogène (7783-06-4)	
FBC - Poissons [1]	(no bioaccumulation expected)
Coefficient de partage n-octanol/eau (Log Pow)	Sans objet.
Coefficient de partage n-octanol/eau (Log Kow)	Sans objet.
Potentiel de bioaccumulation	Aucune donnée disponible.

Monoxyde de carbone (630-08-0)	
Coefficient de partage n-octanol/eau (Log Kow)	Sans objet.

Oxygène (7782-44-7)	
Coefficient de partage n-octanol/eau (Log Pow)	Sans objet.
Coefficient de partage n-octanol/eau (Log Kow)	Sans objet.
Potentiel de bioaccumulation	Ce produit est sans risque sur le plan écologique.

Nitrogen (7727-37-9)	
Coefficient de partage n-octanol/eau (Log Pow)	Sans objet.
Coefficient de partage n-octanol/eau (Log Kow)	Sans objet.
Potentiel de bioaccumulation	Ce produit est sans risque sur le plan écologique.

Méthane (74-82-8)	
Coefficient de partage n-octanol/eau (Log Pow)	1.09
Potentiel de bioaccumulation	Pas de bioaccumulation à attendre en cas de log Kow bas (log Kow<4). Voir section 9.

Linde es un marque commerciale ou un marque déposées de Linde Inc. aux États-Unis et/ou dans d'autres pays.

12.4. Mobilité dans le sol

PTG-4001	
Mobilité dans le sol	Aucune donnée disponible.

Sulfure d'hydrogène (7783-06-4)	
Mobilité dans le sol	Aucune donnée disponible.
Écologie - sol	Dû à sa grande volatilité, la pollution des sols ou eaux par ce produit est improbable. Partition into soil is unlikely.

Monoxyde de carbone (630-08-0)	
Mobilité dans le sol	Aucune donnée disponible.

Oxygène (7782-44-7)	
Mobilité dans le sol	Aucune donnée disponible.
Écologie - sol	Ce produit est sans risque sur le plan écologique.

Nitrogen (7727-37-9)	
Mobilité dans le sol	Aucune donnée disponible.
Écologie - sol	Ce produit est sans risque sur le plan écologique.

Méthane (74-82-8)	
Écologie - sol	Dû à sa grande volatilité, la pollution des sols ou eaux par ce produit est improbable.

12.5. Autres effets néfastes

Effet sur la couche d'ozone : None.

Effet sur le réchauffement planétaire : Contient un (des) gaz à effet de serre, non soumis au Règlement 842/2006/EC.

SECTION 13: Données sur l'élimination

13.1. Méthodes de traitement des déchets

Méthodes de traitement des déchets : Ne pas tenter d'éliminer les quantités résiduelles ou non utilisées. Retourner le contenant au fournisseur.

Recommandations pour le traitement du produit/emballage : Ne pas tenter d'éliminer les quantités résiduelles ou non utilisées. Retourner le contenant au fournisseur.

SECTION 14: Informations relatives au transport

Département des transports (DOT)

Conformément aux exigences du DOT

Description document de transport (DOT) : UN1956 Compressed gas, n.o.s., 2.2

N° ONU (DOT) : UN1956

Nom officiel d'expédition (DOT) : Compressed gas, n.o.s.

Classe (DOT) : 2.2 - Class 2.2 - Non-flammable compressed gas 49 CFR 173.115

Étiquettes de danger (DOT) : 2.2 - Gaz ininflammable



Emballage Non-Vrac DOT (49 CFR 173.xxx) : 302;305

Emballage en Vrac DOT (49 CFR 173.xxx) : 314;315

DOT Symbols : G - Identifies proper shipping name (PSN) requiring the addition of technical name(s) in parentheses following the PSN.

Exceptions d'Emballage DOT (49 CFR 173.xxx) : 306;307

Quantités maximales DOT - Aéronef de passagers/véhicule ferroviaire (49 CFR 173.27) : 75 kg

Quantités maximales DOT - Aéronef cargo seulement (49 CFR 175.75) : 150 kg

Linde es un marque commerciale ou un marque déposées de Linde Inc. aux États-Unis et/ou dans d'autres pays.

DOT Emplacement d'arrimage	:	A - The material may be stowed ‘‘on deck’’ or ‘‘under deck’’ on a cargo vessel and on a passenger vessel.

Indications complémentaires

Numéro du Guide des Mesures d'Urgence (GMU)	:	126
Autres informations	:	Pas d'informations supplémentaires disponibles.
Mesures de précautions pour le transport	:	Éviter le transport dans des véhicules dont le compartiment du chargement n'est pas séparé de la cabine de conduite. S'assurer que le conducteur du véhicule connaît les dangers potentiels du chargement ainsi que les mesures à prendre en cas d'accident ou autre situation d'urgence. Avant de transporter les récipients: - S'assurer qu'il y a une ventilation appropriée. - S'assurer que les récipients sont fermement arrimés. - S'assurer que le robinet de la bouteille est fermé et ne fuit pas. - S'assurer que le bouchon de protection de sortie du robinet (quand il existe) est correctement mis en place. - S'assurer que le dispositif de protection du robinet (quand il existe) est correctement mis en place.

Conformément aux exigences relatives au TMD

Transport des marchandises dangereuses (TMD)

UN-No. (TDG)	:	UN1956
Nom officiel d’expédition (TMD)	:	Compressed Gas, n.o.s.
TMD Classe primaire de danger	:	2.2 - Classe 2.2 - Gaz ininflammables, non toxiques
Indices des quantités limites d'explosifs et des quantités limitées	:	0.125L
Indice véhicule routier de passagers ou indice véhicule ferroviaire de passagers	:	75 L

Transport maritime

N° ONU (IMDG)	:	1956
Nom officiel d’expédition (IMDG)	:	GAZ COMPRIMÉ, N.S.A
Classe (IMDG)	:	2 - Gaz
Quantités limitées (IMDG)	:	120ml
Numéro EmS (1)	:	F-C
N° GSMU	:	620
Numéro EmS (2)	:	S-V

Transport aérien

N° UN (IATA)	:	1956
Nom officiel d’expédition (IATA)	:	Compressed gas, n.o.s.
Classe (IATA)	:	2 - Gases
Instruction "cargo" (ICAO)	:	200
Instruction "passenger" (ICAO)	:	200
Instruction "passenger" - Limited quantities (ICAO)	:	FORBIDDEN
Législation aéronautique civile	:	Gases under pressure/Gases nonflammable nontoxic under pressure(Hazardous materials notice Appended Table 1 Article 194 of the Enforcement Regulations)

SECTION 15: Informations sur la réglementation

15.1. Réglementations fédérales USA

PTG-4001
Listé dans la Section 302 du SARA des Etats-Unis (substances dangereuses) Soumis aux exigences de déclaration de la Loi SARA Section 313 des États-Unis Inscrit dans l'inventaire du TSCA (Toxic Substances Control Act) des États-Unis

Sulfure d'hydrogène (7783-06-4)	
Inscrit dans l'inventaire du TSCA (Toxic Substances Control Act) des États-Unis Listé dans la Section 302 du SARA des Etats-Unis (substances dangereuses) Soumis aux exigences de déclaration de la Loi SARA Section 313 des États-Unis	
Loi SARA Section 302, États-Unis, TPQ (Seuil de procédure d'urgence)	500 lb
Loi SARA Section 313, États-Unis – Déclaration des émissions	1 %

Monoxyde de carbone (630-08-0)
Inscrit dans l'inventaire du TSCA (Toxic Substances Control Act) des États-Unis

Oxygène (7782-44-7)
Inscrit dans l'inventaire du TSCA (Toxic Substances Control Act) des États-Unis

Nitrogen (7727-37-9)
Inscrit dans l'inventaire du TSCA (Toxic Substances Control Act) des États-Unis

Méthane (74-82-8)
Inscrit dans l'inventaire du TSCA (Toxic Substances Control Act) des États-Unis

15.2. Réglementations internationales

CANADA

PTG-4001	
Inscrit sur la liste canadienne DSL (Liste intérieure des substances)	
Classification SIMDUT	Catégorie A – Gaz comprimés

Sulfure d'hydrogène (7783-06-4)	
Inscrit sur la liste canadienne DSL (Liste intérieure des substances)	
Classification SIMDUT	Catégorie A – Gaz comprimés Catégorie B – Division 1 : Gaz inflammable Catégorie D – Division 1, Sous-division A : Matière très toxique Catégorie D –Division 2, Sous-division B : Matière toxique

Monoxyde de carbone (630-08-0)	
Inscrit sur la liste canadienne DSL (Liste intérieure des substances)	
Classification SIMDUT	Catégorie A – Gaz comprimés Catégorie B – Division 1 : Gaz inflammable Catégorie D – Division 1, Sous-division A : Matière très toxique Catégorie D – Division 2, Sous-division A : Matière très toxique

Oxygène (7782-44-7)	
Inscrit sur la liste canadienne DSL (Liste intérieure des substances)	
Classification SIMDUT	Catégorie A – Gaz comprimés Catégorie C – Matières comburantes

Nitrogen (7727-37-9)	
Inscrit sur la liste canadienne DSL (Liste intérieure des substances)	
Classification SIMDUT	Catégorie A – Gaz comprimés

Méthane (74-82-8)	
Inscrit sur la liste canadienne DSL (Liste intérieure des substances)	
Classification SIMDUT	Catégorie A – Gaz comprimés Catégorie B – Division 1 : Gaz inflammable

Réglementations UE

Sulfure d'hydrogène (7783-06-4)
Inscrit dans l'EINECS (European Inventory of Existing Commercial Chemical Substances)

Monoxyde de carbone (630-08-0)
Inscrit dans l'EINECS (European Inventory of Existing Commercial Chemical Substances)

Oxygène (7782-44-7)
Inscrit dans l'EINECS (European Inventory of Existing Commercial Chemical Substances)

Linde es un marque commerciale ou un marque déposées de Linde Inc. aux États-Unis et/ou dans d'autres pays.

Nitrogen (7727-37-9)
Inscrit dans l'EINECS (European Inventory of Existing Commercial Chemical Substances)

Méthane (74-82-8)
Inscrit dans l'EINECS (European Inventory of Existing Commercial Chemical Substances)

Classification selon le règlement (CE) N° 1272/2008 [CLP]
Press. Gas (Comp.) H280

Classification selon les directives 67/548/CEE ou 1999/45/CE
Pas de données supplémentaires.

Directives nationales

Sulfure d'hydrogène (7783-06-4)
Inscrit dans l'AICS (Australian Inventory of Chemical Substances) Inscrit dans l'IECSC (Inventory of Existing Chemical Substances Produced or Imported in China) Listé dans l'inventaire japonais ENCS (Existing New Chemical Substances) Listé dans l'ISHL du Japon (Industrial Safety and Health Law) Inscrit dans l'ECL (Existing Chemicals List) coréenne Inscrit dans le NZIoC (New Zealand Inventory of Chemicals) Inscrit dans le PICCS (Philippines Inventory of Chemicals and Chemical Substances) Listé dans la LDI (Liste de Divulgation des Ingrédients) canadienne Inscrit dans l'INSQ (Mexican National Inventory of Chemical Substances) Répertorié dans le TCSI (répertoire des substances chimiques de Taïwan)

Monoxyde de carbone (630-08-0)
Inscrit dans l'AICS (Australian Inventory of Chemical Substances) Inscrit dans l'IECSC (Inventory of Existing Chemical Substances Produced or Imported in China) Listé dans l'inventaire japonais ENCS (Existing New Chemical Substances) Listé dans l'ISHL du Japon (Industrial Safety and Health Law) Inscrit dans l'ECL (Existing Chemicals List) coréenne Inscrit dans le NZIoC (New Zealand Inventory of Chemicals) Inscrit dans le PICCS (Philippines Inventory of Chemicals and Chemical Substances) Listé dans la LDI (Liste de Divulgation des Ingrédients) canadienne Inscrit dans l'INSQ (Mexican National Inventory of Chemical Substances) Répertorié dans le TCSI (répertoire des substances chimiques de Taïwan)

Oxygène (7782-44-7)
Inscrit dans l'AICS (Australian Inventory of Chemical Substances) Inscrit dans l'IECSC (Inventory of Existing Chemical Substances Produced or Imported in China) Inscrit dans l'ECL (Existing Chemicals List) coréenne Inscrit dans le NZIoC (New Zealand Inventory of Chemicals) Inscrit dans le PICCS (Philippines Inventory of Chemicals and Chemical Substances) Inscrit dans l'INSQ (Mexican National Inventory of Chemical Substances) Répertorié dans le TCSI (répertoire des substances chimiques de Taïwan)

Nitrogen (7727-37-9)
Inscrit dans l'AICS (Australian Inventory of Chemical Substances) Inscrit dans l'IECSC (Inventory of Existing Chemical Substances Produced or Imported in China) Inscrit dans l'ECL (Existing Chemicals List) coréenne Inscrit dans le NZIoC (New Zealand Inventory of Chemicals) Inscrit dans le PICCS (Philippines Inventory of Chemicals and Chemical Substances) Inscrit dans l'INSQ (Mexican National Inventory of Chemical Substances)

Méthane (74-82-8)
Inscrit dans l'AICS (Australian Inventory of Chemical Substances) Inscrit dans l'IECSC (Inventory of Existing Chemical Substances Produced or Imported in China) Listé dans l'inventaire japonais ENCS (Existing New Chemical Substances) Inscrit dans l'ECL (Existing Chemicals List) coréenne Inscrit dans le NZIoC (New Zealand Inventory of Chemicals) Inscrit dans le PICCS (Philippines Inventory of Chemicals and Chemical Substances) Inscrit dans l'INSQ (Mexican National Inventory of Chemical Substances) Listé sur le CICR (Turkish Inventory and Control of Chemicals)

Linde es un marque commerciale ou un marque déposées de Linde Inc. aux États-Unis et/ou dans d'autres pays.

15.3. Réglementations des Etats - USA

PTG-4001()	
USA - Californie - Proposition 65 - Liste des cancérogènes	Non
USA - Californie - Proposition 65 - Toxicité pour le développement	Yes
USA - Californie - Proposition 65 - Reprotoxicité - Femelle	Non
USA - Californie - Proposition 65 - Reprotoxicité - Mâle	Non

Monoxyde de carbone (630-08-0)				
USA - Californie - Proposition 65 - Liste des cancérogènes	USA - Californie - Proposition 65 - Toxicité pour le développement	USA - Californie - Proposition 65 - Reprotoxicité - Femelle	USA - Californie - Proposition 65 - Reprotoxicité - Mâle	NSRL (Concentration sans risque significatif)
Non	Yes	Non	Non	

Sulfure d'hydrogène (7783-06-4)

U.S. - Massachussetts - Liste Right To Know
U.S. - New Jersey - Liste Right To Know des substances dangereuses
U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List
U.S. - Pennsylvania - RTK (Right to Know) List

Monoxyde de carbone (630-08-0)

U.S. - Massachussetts - Liste Right To Know
U.S. - New Jersey - Liste Right To Know des substances dangereuses
U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List
U.S. - Pennsylvania - RTK (Right to Know) List

Oxygène (7782-44-7)

U.S. - Massachussetts - Liste Right To Know
U.S. - New Jersey - Liste Right To Know des substances dangereuses
U.S. - Pennsylvania - RTK (Right to Know) List

Nitrogen (7727-37-9)

U.S. - Massachussetts - Liste Right To Know
U.S. - New Jersey - Liste Right To Know des substances dangereuses
U.S. - Pennsylvania - RTK (Right to Know) List

Méthane (74-82-8)

U.S. - Massachussetts - Liste Right To Know
U.S. - New Jersey - Liste Right To Know des substances dangereuses
U.S. - Pennsylvania - RTK (Right to Know) List

SECTION 16: Autres informations

Date de révision : 05/17/2024

Linde es un marque commerciale ou un marque déposées de Linde Inc. aux États-Unis et/ou dans d'autres pays.

Autres informations	:	Lorsqu'on mélange deux produits chimiques ou plus, des dangers imprévus peuvent être créés. Obtenir et évaluer les renseignements de sécurité pour chaque composant avant de procéder au mélange. Consulter un hygiéniste industriel ou d'autres personnes compétentes lorsqu'on évalue le produit final. Avant d'utiliser des matières plastiques, confirmer leur compatibilité avec ce produit. Linde Canada Inc. demande aux utilisateurs de ce produit de bien étudier cette fiche signalétique et d'être conscients des dangers du produit et des précautions à prendre. Afin de promouvoir l'utilisation sécuritaire de ce produit, l'utilisateur doit 1) informer son personnel, ses agents et ses sous-traitants de l'information contenue dans cette fiche signalétique et de tout danger ou précaution à prendre, 2) fournir cette même information à tous ses clients utilisateurs de ce produit, et 3) demander à ces derniers de transmettre la même information à leurs employés et à leurs clients. Les opinions exprimées ici sont celles d'experts qualifiés de Praxair Canada inc. Nous croyons que l'information contenue dans ce document est en vigueur à la date de cette fiche de données de sécurité (FDS). Puisque l'utilisation de ces informations et les conditions d'utilisation ne sont pas sous le contrôle de Praxair Canada inc, il est dans l'obligation de l'utilisateur de déterminer les conditions d'utilisation sécuritaire du produit. Linde FDS sont meublées à la vente ou la livraison par Linde ou les distributeurs et les fournisseurs qui conditionnent et vendent nos produits indépendants. Pour obtenir actuelle SDD pour ces produits, contactez votre représentant Linde des ventes, le distributeur local, ou fournisseur, ou le télécharger à partir www.lindecanada.ca. Linde es un marque commerciale ou un marque déposées de Linde Inc. aux États-Unis et/ou dans d'autres pays.

SDS US_and_Canada

Ces informations étant basées sur nos connaissances actuelles et décrivant le produit pour les seuls besoins de la santé, de la sécurité et de l'environnement. Elles ne doivent donc pas être interprétées comme garantissant une quelconque propriété spécifique du produit